





packetSENSE

PIR Motion Sensor

The packetSENSE PIR Motion Sensor is a highly advanced and reliable device that utilizes passive infrared technology to detect motion or occupancy.

It detects any movement within its range and promptly sends a status update via the LoRaWAN® network, ensuring consistent awareness of the changes in the environment. In addition to its core motion detection capabilities, this device supports door and window status detection and temperature and humidity monitoring.

These additional features make the packetSENSE PIR Motion Sensor an ideal choice for use in numerous settings, including offices, homes, and industrial buildings.

Features

- LoRaWAN® compatible
- Endurance of up to 5 years
- Flexible mountings
- Wide Temperature Range
- Extreme Battery Life

Applications

- Smart Office
- Smart Lighting
- Intrusion Alarm
- Intelligent Factory
- Occupancy Detection
- Environmental Monitoring
- On-Site Presence Monitoring
- Door/Window Status Detection



Packetworx IoT Technology Hub G/F iSquare Building, 15 Meralco Ave Ortigas, Pasig City, 1605, Philippines

(+632) 7971-9211 | (+63) 917-189-7613

Technical Specification

LoR

LoRa		
	Frequency	EU868/AS923-1/AS923-3
	Tx Power	Max. 21dBm
	Sensitivity	-137dBm @ SF12 300bps
	LoRa Communication Distance	Up to 7 km (in urban open space)
Blu	etooth	
	Bluetooth® (BLE)	4.0
	Tx Power	Max. 4dBm
	BLE Communication Distance	Up to 50m in free space
PIR Performance		
	PIR Detection Range	Max. 8m
	PIR Detection Angle	Horizontal 120°, vertical 60°
Temperature and Humidity		
	Temperature Measure Accuracy	±0.3(0-60);
		±0.5(-20-0);
		±1(-3020)
	Humidity Measure Accuracy	±3% RH (10% RH - 90% RH);
		±4.5% RH - ±3% RH (0% RH - 10% RH);
		±3% RH - ±3.8% RH (90% RH - 95% RH)
Application		
	Operating Temperature	-30 °C − 60 °C
	Operating Humidity	0% - 95%
	Installation Ways	Double-sided tape/Screws
Door/Window Detection Performance		
	Recommended Installation Gap	< 10mm
	Detection distance	20mm
Physical Specification		
	Dimension	70mm x 50mm x 38mm
	Shell Material	ABS+PC
	Color	White
Power		
	Power Supply	2*AA ER14505 5200mAh Replaceable battery
	Operating Current	< 120mA